

4000 MOTION 10W-30

Gasoline or diésel Engine Oil
"Fuel Economy" performance
Mineral

TYPE OF USE

Specially designed for vehicles requiring SAE 10W-30 viscosity oil, low HTHS and Fuel Economy performance. Suitable for all types of Gasoline engines, with injection or carburetor, and catalytic converter. Suitable for all type of fuels. These oils may be unsuitable for use in some engines. Refer to the owner manual or handbook if in doubt.

PERFORMANCES

STANDARDS ACEA A1 / B1
 API SL / CF

The ACEA A1/B1 performance requires fuel economy and low emission performance from the lubricant for better engine output. MOTUL 4000 Motion 10W-30 reduces friction in the engine.

Detergent, dispersive agents and anti-oxidation additives are particularly reinforced to resist over extended oil change required by manufacturers for new car models.

Very efficient anti-deposit and anti-black sludge properties to help maintaining the engine clean.
 Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.
 MOTUL 4000 Motion 10W-30 can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 20°C (68°F)	ASTM D1298	0.865

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

4000 MOTION 10W-30**Gasoline or diésel Engine Oil
"Fuel Economy" performance
Mineral**

Viscosity at 40°C (104°F)	ASTM D445	74.6 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	11.1 mm ² /s
Viscosity Index	ASTM D2270	137.0
Pour point	ASTM D97	-42.0 °C / -44.0 °F
TBN	ASTM D2896	9.8 mg KOH/g
Flash point	ASTM D92	228.0 °C / 442.0 °F