



4000 MOTION 15W-40

**Gasoline and Diesel engine oil
Mineral**

TYPE OF USE

Specially designed for cars powered by Gasoline and Diesel engines, naturally aspirated or turbocharged, indirect or direct injection, carburetor or injection, with or without catalytic converter.

Suitable for all type of fuels: leaded or unleaded Gasoline, Ethanol, LPG, Diesel and biofuels.

PERFORMANCES

STANDARDS ACEA A3 / B3
API SERVICE SN

APPROVALS MERCEDES-BENZ MB-Approval 229.1

The standard API SN is more stringent than API SM and SL in terms of ageing resistance (average drain interval increased), requires anti-oxidation properties that maintain a constant viscosity avoiding sludge and deposits in the crankcase, anti-wear properties and dispersant power.

Detergent, dispersive agents and anti-oxidation additivation are particularly reinforced to ensure longer drain intervals, required by manufacturers for the new model of cars.

Very efficient anti-deposit and anti-black sludge power which maintains a clean engine.

Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

MOTUL 4000 Motion 15W-40 can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	15W-40
-----------------	-----------	--------

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com

07/21



4000 MOTION 15W-40

Gasoline and Diesel engine oil
Mineral

Density at 20°C (68°F)	ASTM D1298	0.869
Viscosity at 40°C (104°F)	ASTM D445	113.2 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.8 mm ² /s
Viscosity Index	ASTM D2270	135.0
Pour point	ASTM D97	-42.0 °C / -44.0 °F
TBN	ASTM D2896	9.8 mg KOH/g
Flash point	ASTM D92	238.0 °C / 460.0 °F