

**TYPE OF USE**

High performance bikes, sports bikes, street & road bikes, trails, off road bikes, enduro, trial...fitted with 4 stroke engines, integrated gearbox or not, wet or dry clutch, engines meeting Euro 2, 3, 4 or 5 emission regulation, fitted with exhaust gas after treatment systems : catalytic converters, air injection into exhaust pipe...

Recommended for specific HONDA, YAMAHA engines requiring SAE 10W-30 viscosity grade oil.

Other uses: street bikes without catalytic converters, scooters, ATV's, UTV's...

**PERFORMANCES**

STANDARDS API SN / SM / SL / SJ / SH / SG

PERFORMANCES JALOS MA2 under N°M033MOT160

**Protection**

Ester Technology:

- Low traction coefficient Ester to minimize engine internal friction losses and improve performance.
- Synergy of Ester with anti-wear additives and improved shear resistance for improved gear protection and life time.

100% Synthetic lubricant for improved oil film resistance at high temperatures and high revs.

Optimized Phosphorus and Sulfur content (JASO MA2 < 1200 ppm) for better operating conditions of catalytic converters.

The innovative anti-wear additives package provides outstanding gearbox protection. FZG Gear Test results: Pass FLS>14. The **FZG** (Forschungsstelle für Zahnrad und Getriebebau) Test, evaluates fluid lubricating and wear protection properties at the interface of a loaded set of gears. Lubricants are then graded based on their "Failure Load Stage" or FLS rating from FLS 1 (very poor result) up to FLS 14 (outstanding result).

**Comfort**

JASO has created its own 4-stroke motorcycle standard -JASO T903- which has three grades MA, MA1 and MA2.

JASO MA2 offers the most efficient friction levels to guarantee the clutch engagement during the three riding modes: Starting, Acceleration and Constant Speed.



## 7100 4T 10W-30

**High Performance Motorcycle Lubricant**  
**100% Synthetic – Ester**

### RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.  
Can be mixed with synthetic or mineral lubricants.

### PROPERTIES

Color	Visual	Red
Viscosity grade	SAE J 300	10W-30
Density at 20°C (68°F)	ASTM D1298	0.859
Viscosity at 40°C (104°F)	ASTM D445	73.7 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	11.4 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	147.0
Pour point	ASTM D97	-33.0 °C / -27.0 °F
TBN	ASTM D2896	8.4 mg KOH/g
Flash point	ASTM D92	228.0 °C / 442.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br\>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com