

GARDEN 2T HI-TECH**2 Stroke Engine Lubricant for Motorised Garden Tools
Technosynthese®****TYPE OF USE****Specially formulated for 2 Stroke engine garden tools.****Suitable with leaded or unleaded gasoline.****Motor cultivator, chain saw, lawn mower, ground clearing machine...**

MOTUL GARDEN 2T Hi-Tech exceeds specifications of ISO-L-EGD, JASO FC and API TC standards, and is consequently recommended for engines working under very severe conditions or at high revs.

PERFORMANCES

STANDARDS	API TC
	ISO -L-EGD
	JASO FD

Contains synthetic products with very high combustion properties to reduce smoke and deposits.

Pre-diluted lubricant which mixes instantaneously with gasoline and remains stable.

Reinforced anti-rust and anti-corrosion properties.

Reduces deposits in exhaust pipes and on pistons.

Prevents spark plug from fouling.

RECOMMENDATIONS

Premix ratio : from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements.

PROPERTIES

Color	Visual	Red
Density at 20°C (68°F)	ASTM D1298	0.859

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



GARDEN 2T HI-TECH

**2 Stroke Engine Lubricant for Motorised Garden Tools
Technosynthese®**

Viscosity at 40°C (104°F)	ASTM D445	65.6 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	9.5 mm ² /s
Viscosity Index	ASTM D2270	135.0
Flash point	ASTM D92	151.0 °C / 304.0 °F