

GARDEN 4T 5W-30

**4 Stroke Engine Lubricant for Motorized Garden Tools
Gasoline and Diesel Engine
Technosynthese® - SAE 5W-30**

TYPE OF USE

Specially formulated for motorized garden tools and small farming equipment.

All Gasoline and Diesel 4 stroke engines, naturally aspirated or turbocharged.

Lawn mowers, motor mowers, ride on mowers, tillers, light tractors...etc.

Especially designed for small snow removal equipment and tools, snow blowers...etc. working in very cold climate.

Suitable for all types of fuel: leaded and unleaded gasoline, Diesel fuel, Ethanol, biofuels.

All types of 4 stroke gasoline engines with or without catalytic converter.

PERFORMANCES**STANDARDS**

API SL / CF

Technosynthese® multigrade lubricant reinforced with synthetic base stocks for improved engine protection in all temperature conditions

The SAE 5W-30 viscosity grade delivers easy cold start up while providing perfect protection in hot conditions and Fuel Economy benefits

Ensures the engine cleanliness

Protection during wintering

Dispersant and detergent properties

Anti-oxidation, Anti-wear properties.

Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Oil change: According to manufacturers' requirements and adjust according to your own use.

MOTUL GARDEN 4T 5W-30 can be mixed with synthetic or mineral lubricants.



GARDEN 4T 5W-30

**4 Stroke Engine Lubricant for Motorized Garden Tools
Gasoline and Diesel Engine
Technosynthese® - SAE 5W-30**

PROPERTIES

Viscosity grade	SAE J 300	5W-30
Density at 20°C (68°F)	ASTM D1298	0.856
Viscosity at 40°C (104°F)	ASTM D445	69.5 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	12.1 mm ² /s
Viscosity Index	ASTM D2270	169.0
Pour point	ASTM D97	-39.0 °C / -38.0 °F
TBN	ASTM D2896	10.1 mg KOH/g
Flash point	ASTM D92	220.0 °C / 428.0 °F