

GARDEN 4T SAE 30**4 Stroke Engine Oil for Motorized Garden Tools
Mineral****TYPE OF USE****Specially formulated for motorized garden tools and small farming equipment.****All Gasoline & Diesel 4 Stroke Engines.**

Lawn mowers, motor mowers, tillers, light tractors,...

Suitable for all type of fuels: leaded and unleaded gasoline, Diesel fuel, Ethanol, biofuels.

All types of 4 stroke engines with or without catalytic converter.

PERFORMANCES**STANDARDS**

API SG / CD

Ensures the engine cleanliness.

Protection during wintering.

Dispersant and detergent properties.

Good cold starting, perfectly stable in hot engine.

Anti-wear, Anti-oxidation properties.

Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Oil change: According to manufacturers' requirements and tune to your own use.

MOTUL GARDEN 4T SAE 30 can be mixed with synthetic or mineral lubricants.

PROPERTIES

Viscosity grade	SAE J 300	30
Density at 20°C (68°F)	ASTM D1298	0.884
Viscosity at 40°C (104°F)	ASTM D445	81.5 mm ² /s

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

GARDEN 4T SAE 30**4 Stroke Engine Oil for Motorized Garden Tools
Mineral**

Viscosity at 100°C (212°F)	ASTM D445	10.5 mm ² /s
Viscosity Index	ASTM D2270	112.0
Pour point	ASTM D97	-21.0 °C / -5.8 °F
TBN	ASTM D2896	7.8 mg KOH/g
Flash point	ASTM D92	224.0 °C / 435.2 °F