

MOTUL IRIX MULTI 200

**High Performance Multipurpose Grease
NLGI 2 – Extreme Pressure
Lithium**

TYPE OF USE

High performance multipurpose grease recommended for the lubrication of roller bearings, plain bearings, thrust bearings, gears, electric motors, winches, bushings, wheel bearings, universal joints, ball joints, chassis lubrication in heavy- and light-duty, automobiles, landscaping, agricultural, motorcycle and powersports equipment operating under normal to severe conditions.

Operating temperatures for long-term lubrication: from -20 °C / -4 °F to +130 °C / +266 °F.

PERFORMANCES

High quality multipurpose grease formulated with mineral base oil stock, lithium soap and Extreme Pressure, anti-wear, anti-oxidation & anti-corrosion additives.

Protects against corrosion.

High pressure load capacity according to FAG FE-9 test.

Water resistance with reinforced adhesiveness.

Designation DIN 51502: KP 2 K-20

PROPERTIES

Color	Visual	Orange
Drop point	DIN ISO 2176	> 190 °C / 374 °F
Consistency grade	DIN 51818	NLGI 2
Soap		Lithium
Base oil viscosity at 40°C	DIN 51562	180.0 mm ² /s
Base oil viscosity at 100°C	DIN 51562	13.0 mm ² /s
Penetrability - 60 cycles	ASTM D217	265 / 295 1/10 mm
TIMKEN Test - Load	ASTM D2509	178.0 N
Copper Strip Corrosion	ASTM D4048	1 / 100

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



MOTUL IRIX MULTI 200

High Performance Multipurpose Grease
NLGI 2 – Extreme Pressure
Lithium

VKA welding load	DIN 51350:4	3,400.0 N
Water washout	DIN 51807 T1	1 / 90