



MOTUL LHM+

Mineral fluid for CITROËN hydraulic systems
Mineral

TYPE OF USE

Mineral fluid for the lubrication of hydropneumatic suspension and braking systems, green-painted, of CITROËN vehicles only (since 1966).

PERFORMANCES

PERFORMANCES CITROËN LHM

Improved performance at low temperature compare to conventional LHM fluids.
Extreme stability.
Anti-corrosion.
Anti-foam.
Anti-wear.

RECOMMENDATIONS

To be used only in green-painted hydraulic circuits designed by CITROËN.
Not to be used in black-painted hydraulic circuits.
Not to be mixed with synthetic or other fluids.

PROPERTIES

Color	Visual	Green
Density at 20°C (68°F)	ASTM D1298	0.830
Viscosity at 100°C (212°F)	ASTM D445	6.1 mm ² /s
Viscosity Index	ASTM D2270	335.0
Pour point	ASTM D97	-60.0 °C / -76.0 °F
Viscosity at -40°C (-40°F)		1,056.0 mm ² /s

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com



MOTUL LHM+

Mineral fluid for CITROËN hydraulic systems
Mineral

Flash point

ASTM D92

115.0 °C / 239.0 °F