

**MICRO 2T**

**2 Stroke engine lubricant for RC vehicles**  
**100% Synthetic**  
**Miscible with methanol**

**TYPE OF USE**

100% Synthetic lubricant specially formulated for 2 Stroke engines RC – Radio Controlled vehicles: RC cars, boats, planes, etc...  
Entirely miscible with nitromethane, methanol, ether...

**PERFORMANCES**

Highly resistant to mechanical efforts, it avoids sticking.  
Keeps the engine clean (no deposits).  
Very stable during storage and cold weather.  
Miscible with nitromethane, methanol and ether.  
Anti-corrosion. Anti-rust.

**RECOMMENDATIONS**

MOTUL MICRO 2T can be mixed with methanol, nitromethane or ether according to the following proportions (15 to 20% depending on the use and manufacturer's recommendations):

MOTUL MICRO 2T	15 - 20%
METHANOL	70 - 75%
NITROMETHANE	10%

To be adjusted according to your own use or experience.

**PROPERTIES**

Color	Visual	Red
Density at 20°C (68°F)	ASTM D1298	0.993

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



## MICRO 2T

**2 Stroke engine lubricant for RC vehicles**  
**100% Synthetic**  
**Miscible with methanol**

Viscosity at 40°C (104°F)	ASTM D445	180.0 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	31.8 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	213.0
Pour point	ASTM D97	-30.0 °C / -22.0 °F
Flash point	ASTM D92	225.0 °C / 437.0 °F