

OUTBOARD 2T

2 stroke engine oil
Outboard
NMMA TC-W3
Mineral

TYPE OF USE

For Outboard 2 stroke engines lubricated by premix or by injector : EVINRUDE, JOHNSON, MARINER, MERCURY, SEAGULL, SELVA, SUZUKI, TOHATSU, YAMAHA...
For 2 stroke PWC engines: BRP, KAWASAKI, YAMAHA....
Suitable for unleaded gasoline.

PERFORMANCES

STANDARDS API TSC 4
 NMMA TC-W / TC-W3 under n° RL-13899W / TC-WII

Exceeds the NMMA TC-W3 latest standard level (National Marine Manufacturing Association - ex BIA) which regroups main outboard and Personal Water Craft manufacturers.

Reduces frictions and wear to increase engine life.

Formulated to go through all injector systems.

Mixes instantaneously with gasoline and remains stable.

A complete additivation system to avoid spark plug fouling, carbon deposit.

Blue colored for an easy detection in gasoline.

RECOMMENDATIONS

Mixing ratio for premix lubrication : from 1% to 2% according to manufacturers' requirements and adjust according to your own use.

PROPERTIES

| | | |
|------------------------|------------|-------|
| Color | Visual | Blue |
| Density at 20°C (68°F) | ASTM D1298 | 0.859 |

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

**2 stroke engine oil
Outboard
NMMA TC-W3
Mineral**

| | | |
|----------------------------|------------|-------------------------|
| Viscosity at 40°C (104°F) | ASTM D445 | 57.7 mm ² /s |
| Viscosity at 100°C (212°F) | ASTM D445 | 9.1 mm ² /s |
| Viscosity Index | ASTM D2270 | 137.0 |
| Pour point | ASTM D97 | -36.0 °C / -33.0 °F |
| Flash point | ASTM D92 | 154.0 °C / 309.0 °F |