



POWERJET 2T

**2 Stroke engine oil for Jet Ski
Technosynthese® - NMMA TC-W3**

TYPE OF USE

For Jet Ski, Water Scooter, PWC – Personal Water Craft, Watercraft,... 2 Stroke engines, Direct Injection or carburetors, lubricated by premix or by oil injector: KAWASAKI, YAMAHA, POLARIS, BRP...
Suitable for oil injector systems or premix, using all types of gasoline fuels: leaded or unleaded, with or without Ethanol, biofuels.

PERFORMANCES

STANDARDS NMMA TC-W / TC-W3 / TC-WII

Synthetic lubricant Technosynthese® reinforced formulation for improved protection and longer engine life time.

Exceeds the NMMA TC-W3 upper standard level, low smoke.

"Low Ash" technology protects the engine against carbon deposits build-ups, spark plug fouling, exhaust port and piston rings blocking.

Mixes instantaneously with gasoline and remains stable.

Blue colored for an easy detection in Gasoline.

RECOMMENDATIONS

Mixing ratio for premix lubrication: from 1% to 2% according to manufacturers' requirements and adjust according to your own use.

PROPERTIES

Color	Visual	Blue
Density at 20°C (68°F)	ASTM D1298	0.859
Viscosity at 40°C (104°F)	ASTM D445	58.6 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	9.2 mm ² /s

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



POWERJET 2T

**2 Stroke engine oil for Jet Ski
Technosynthese® - NMMA TC-W3**

Viscosity Index	ASTM D2270	137.0
Pour point	ASTM D97	-39.0 °C / -38.0 °F
Flash point	ASTM D92	151.0 °C / 304.0 °F